



FRAMED CABINET STANDARD FEATURES

- Face frame, stiles and rails are 3/4" thick solid wood, and 1-1/2" wide.
- All doors are pre-hung with concealed adjustable hinges
- Cabinet sides are 1/2" thick plywood
- Adjustable shelves are 3/4" thick birch plywood, 5mm holes for shelf support
- All cabinet backs are 1/4" birch plywood dadoed into the sides
- All drawers are constructed with 5/8" thick solid wood drawer sides
- Toe kicks are 1/2" thick birch plywood, and 4 1/2" high
- Standard drawer guides are 75 lbs. capacity, epoxy-coated, double-captive, under mount drawer guides.
- Custom sizing is available



Drawer Box Feature

English Dovetailed Joints and dados, Locking the bottom in place and giving each drawer added strength and durability



Hinge Feature

Concealed adjustable hinges to enhance the beauty of the cabinet and are adjustable, horizontally and vertically



Drawer Slide Feature

Drawer slides are 75 lbs. capacity, epoxy coated, double-captive, under mount drawer guides. These guides are self-closing and are side adjustable using the back mounting blocks




Door Feature

3/4" thick solid hardwood frame and 1/4" thick MDF core veneer center panel

Shaker, slab & other Styles are available upon request.




1. Doors- 3/4" thick solid wood frame with 1/4" thick center panel
2. Drawer fronts - 3/4" thick solid wood frame with 1/4" thick center panel
3. Face frame - 3/4" solid wood
4. Adjustable shelves - 3/4" plywood
5. Under mount drawer guides.
6. Solid wood drawer boxes
7. Back - 1/4 thick plywood
8. Sides - 1/2" thick birch plywood
9. Concealed adjustable hinges
10. Interior to match exterior stain




Door Construction

- A. Frames are tongue and groove, glued and pinned under pressure.
- B. 1/4" thick MDF core veneer center panel, free-floating



Face Frame Construction

- C. 3/16" furniture offset
- D. 3/4" thick x 1-1/2" wide solid hardwood face frames
- E. Blind mortise and tenon joints are glued and pinned under pressure



Drawer Construction

All drawers are constructed of 5/8" thick solid hardwood with dovetail joints on all four corners. A 5mm plywood core drawer bottom is fully captured in grooves on all four edges. The bottom is further secured using adhesive and fasteners. Drawer fronts are fastened to the box using screws

